



58, Paige Close, The Meadows, Watlington
King's Lynn, Norfolk PE33 0TQ
Tel 01553 811977 Fax 01553 811004 Mobile 07768506297
E-mail: sales@manualhandlingsolutions.co.uk
www.manualhandlingsolutions.com

Eat Natural MezzLift Specification – 250kg

Maximum Working Load	250kg
Travel	2940mm floor to floor
Platform Size	850mm x 1650mm to suit two trolleys
Platform Guarding	900mm high frames, three sides to suit loading direction
Lift Speed	0.3 m/s
Number of stops	2 (ground and mezzanine)
Power Supply Required	240v, 20amp, 1 phase terminated in a double pole isolator switch
Controls	Push to run controls adjacent to the gates at both levels
Drive Type	Chain drive, hydraulic motor, Additional independent fall arrest system
Loading Configuration	On/Off same side
Pit	None – loading via 50mm ramp
External Shaft Size	1930mm x 1420mm
Shaft Enclosure	Self supporting 1" x 1" mesh shaft
Door Type	2000mm Clear height double gate, mesh filled. Lift gates are protected by electrical interlocks to prevent access to the shaft unless the platform is docked at the appropriate level
Documentation	CE Mark with Declaration of Conformity Operation and Maintenance Manual issue on completion LOLER Report of Thorough Examination and Test issued on commission
Training	Operator training carried out on completion

